INDUSTRIAL HOSE

GLOBAL

GREEN CORRUGATED SUCTION HOSE

TUBE: PVC, Nitrile blend (TPR), smooth, black

REINFORCEMENT: PVC helix

COVER: Corrugated, green, TPR covered

exterior counterclockwise helix. COLOR: Black with green helix TEMP. RANGE: -30°F to +150°F

FEATURES: Oil resistant TRP, extremely flexible and light weight. Resists cracking due to addition of weather, ozone and UV resistant plasticizors. Exceeds chemical

resistance of EPDM/PVC.

APPLICATION: Liquid suction hose for agricultural irrigation, septic suction, portable toilet cleanout and petroleum spill.



PART #	DESCRIPTION	PACK
I15-215150	1-1/2GREEN CORRUG.SUCTION HOSE	(B)
115-215200	2" GREEN CORRUG.SUCTION HOSE	(B)
115-215250	2-1/2GREEN CORRUG.SUCTION HOSE	(B)
115-215300	3" GREEN CORRUG.SUCTION HOSE	(B)
115-215400	4" GREEN CORRUG.SUCTION HOSE	(B)
I15-215600	6" GREEN CORRUG.SUCTION HOSE	(B)

FDA CLEAR SUCTION HOSE

COLOR: Clear wall & Clear helix
TEMP. RANGE: -10°F to +130°F
FEATURES: High quality materials
conforming to FDA recipes are used. Good
adhesion between soft wall & helix due to

simultaneous adhesion.

APPLICATION: Food Processing, conditions

requiring see through flow.



PART #	DESCRIPTION	<u>PACK</u>
I15-216150	1-1/2FDA CLEAR SUCTION HOSE	(B)
I15-216200	2" FDA CLEAR SUCTION HOSE	(B)
I15-216250	2-1/2FDA CLEAR SUCTION HOSE	(B)
I15-216300	3" FDA CLEAR SUCTION HOSE	(B)
I15-216400	4" FDA CLEAR SUCTION HOSE	(B)



GLOBAL INDUSTRIAL PRODUCTS