

LAMALLOY L-9[®] HEX NUTS



- GREATER TIGHTENING TO RESIST LOOSENING DUE TO SHOCK AND VIBRATION
 - ADDITIONAL THREADS
 - JUST THE RIGHT PLASTICITY – NOT TOO HARD, NOT TOO SOFT
- EASIER TO INSTALL AND REMOVE
 - 30% THICKER
 - MORE WRENCHING SURFACE
- MAXIMUM PROTECTION AGAINST RUST AND CORROSION

**LAMALLOY L-9[®] HEX NUTS ARE DESIGNED TO WORK WITH
LAMALLOY L-9[®] CAP SCREWS TO GIVE YOU SAFE, TIGHT ASSEMBLIES.**



GLOBAL INDUSTRIAL PRODUCTS


NUTS

LAMALLOY L-9® HEX NUTS

Maximum protection against rust and corrosion

FULL CHAMFERED
For easier wrenching

FULL FINISHED
(not semi-finished)



CLEAN, BURR FREE THREADS
cold formed for extra strength

WASHER FACED
For 100% seating

National fine (SAE) & National Coarse (USS) Threads

EXCEEDS FEDERAL SPECIFICATIONS:
FF-N-836 TYPE II STYLE 1

USS – Coarse Threads

PART #	DESCRIPTION	PACK
N05-545810	1/4 USS L-9 HEX NUT	(BAA)
N05-545812	5/16 USS L-9 HEX NUT	(BAA)
N05-545814	3/8 USS L-9 HEX NUT	(BAA)
N05-545816	7/16 USS L-9 HEX NUT	(BAA)
N05-545818	1/2 USS L-9 HEX NUT	(FA)
N05-545820	9/16 USS L-9 HEX NUT	(FA)
N05-545822	5/8 USS L-9 HEX NUT	(CF)
N05-545824	3/4 USS L-9 HEX NUT	(CF)
N05-545826	7/8 USS L-9 HEX NUT	(BA)
N05-545828	1" USS L-9 HEX NUT	(BA)
N05-545830	1-1/8 USS L-9 HEX NUT	(F)
N05-545832	1-1/4 USS L-9 HEX NUT	(F)
N05-545834	1-1/2 USS L-9 HEX NUT	(F)

SAE – Fine Threads

PART #	DESCRIPTION	PACK
N08-545784	1/4 SAE L-9 HEX NUT	(BAA)
N08-545786	5/16 SAE L-9 HEX NUT	(BAA)
N08-545788	3/8 SAE L-9 HEX NUT	(BAA)
N08-545790	7/16 SAE L-9 HEX NUT	(BAA)
N08-545792	1/2 SAE L-9 HEX NUT	(FA)
N08-545794	9/16 SAE L-9 HEX NUT	(FA)
N08-545796	5/8 SAE L-9 HEX NUT	(CF)
N08-545798	3/4 SAE L-9 HEX NUT	(CF)
N08-545800	7/8 SAE L-9 HEX NUT	(BA)
N08-545802	1" SAE L-9 HEX NUT	(BA)
N08-545804	1-1/4 SAE L-9 HEX NUT	(F)



GLOBAL INDUSTRIAL PRODUCTS