

## Access Valves

### Advantages

Access Valves are designed to offer convenient low cost access ports for Refrigeration service. All Access Valves feature 1/4" SAE male flare access ports and are furnished with a finger tight quick seal cap. For greater flexibility, all Tees and Crosses are machined to receive an access core in all 1/4" SAE flare ends. This allows for 2 or more access connections in one fitting plus greater flexibility in the positioning of the valves. All Access Valves with pipe connections have internal ODS solder cups so that these valves may be installed in either of 2 ways.

### Applications

Access Valves may be installed in any position on either high or low side for quick testing, pressure checking, purging or charging.

### Valve Bodies

Straight Access Valve bodies are manufactured from brass rod CA360 or CA345. Shaped Access Valve bodies are manufactured from brass forge rod CA377. All Access Valve bodies are machined in accordance with ARI standard 720-76.

### Valve Core

Parker valve cores meet ARI standard 720-76 and are designed for use with all fluorocarbon refrigerants such as R-12, R-22 and R-502 and are resistant to oils, alkalis and dilute mineral acids.

### Working Pressure and Temperature Ranges


Up to 500 PSI  
-40°F to +400°F

### Order

By part number and name.

### Nomenclature

Part numbers are constructed from symbols that identify the style and size of the valve. The first series of letters identifies the style and type valve. The second series of numbers describes the size.



### Sizes

Tube sized are determined by the number of sixteenths of an inch in the tube O.D.

### Special Fittings

Fitting configurations and/or sizes other than those shown in the catalog can be furnished. It is suggested that a print or sketch be submitted with the inquiry.


### Pricing

Only items priced in current supplementary price list PL3501 are carried in stock. Price and delivery for non-stock items furnished on request for specified quantity.

## Access Valves


### Extended Copper Tube AVUSE

PART NO.	CONNECTION SIZE
AVUSE-2	1/8" O.D. Tube
AVUSE-3	3/16" O.D. Tube
AVUSE-4	1/4" O.D. Tube
AVUSE-5	5/16" O.D. Tube
AVUSE-6	3/8" O.D. Tube
AVUSE-8	1/2" O.D. Tube
AVUSE-9	1/8" O.D. Tube; Additional steps on body for 3/16", 1/4", 5/16", 3/8" O.D. Tube. 3/16", 1/4", or 5/16" Solder Fitting/Swaged Tube.
AVUSE-11	3/16" O.D. Tube; Additional steps on body for 1/4" or 3/8" Solder Fittings/Swaged Tubes 5/16" O.D. Tube.




### Solder Tee AVTS

PART NO.	CONNECTION SIZE
AVTS-4	1/4" O.D. Tube or 3/8" Solder Fitting/Swaged Tube
AVTS-5	5/16" O.D. Tube or 3/8" Solder Fitting/Swaged Tube
AVTS-6	3/8" O.D. Tube or 1/2" Solder Fitting/Swaged Tube
AVTS-8	1/2" O.D. Tube or 5/8" Solder Fitting/Swaged Tube



### Extended Solder Tee AVTSL

PART NO.	CONNECTION SIZE
AVTSL-4	1/4" O.D. Tube/Solder 3/16", 1/4" & 5/16" Tube
AVTSL-5	5/16" O.D. Tube/Solder 1/4", 5/16" & 3/8" Tube
AVTSL-6	3/8" O.D. Tube/Solder 5/16", 3/8" & 7/16" Tube




### Full Union AVU2

PART NO.	CONNECTION SIZE
AVU2-4	1/4" O.D. Flare Tube With Forged Flare Nut



### Bulkhead Union AVU2BH

PART NO.	CONNECTION SIZE
AVU2BH-4	1/4" Bulkhead Access X 1/4" SAE With Forged Nut




### Bulkhead Solder Union AVUS3BH

PART NO.	CONNECTION SIZE
AVUS3BH-4	1/4" Bulkhead Access X 3 Way ODS




**Forged Union Tee AVT2**

PART NO.	CONNECTION SIZE
AVT2-4	1/4" Access All Ends With 2 Forged Flare Nuts and One Core and Cap




**Forged Branch Tee AVT1**

PART NO.	CONNECTION SIZE
AVT1-2	1/8" Male Pipe or 1/4" O.D. Solder on Branch x 1/4" Access Both Ends With One Core and Cap
AVT1-4	1/4" Male Pipe or 5/16" O.D. Solder on Branch x 1/4" Access Both Ends With One Core and Cap




**Male Connector AVU1**

PART NO.	CONNECTION SIZE
AVU1-2	1/8" Male Pipe or 1/4" O.D. Solder
AVU1-4	1/4" Male Pipe or 5/16" O.D. Solder




**Access Valve Assembly AVUIFI**

PART NO.	CONNECTION SIZE
AVUIFI-4	7/16-20 SAE Straight thread O-Ring Port Note: Standard o-ring is neoprene. Consult Brass Products Division for optional o-rings




**Forged Male Elbow AVE1**

PART NO.	CONNECTION SIZE
AVE1-2	1/8" Male Pipe or 1/4" O.D. Solder




**Forged Male Run Tee AVT3**

PART NO.	CONNECTION SIZE
AVT3-2	1/8" Male Pipe or 1/4" O.D. Solder on Run x 1/4" Access on Run and Branch With One Core and Cap
AVT3-4	1/4" Male Pipe or 5/16" O.D. Solder on Run x 1/4" Access on Run and Branch With One Core and Cap



**Forged Male Cross AVC1**


PART NO.	CONNECTION SIZE
AVC1-2	1/8" Male Pipe or 1/4" O.D. Solder x 1/4" Access on all Flare Ends With One Core and Cap
AVC1-4	1/4" Male Pipe or 5/16" O.D. Solder x 1/4" Access on all Flare Ends With One Core and Cap



# Access Valves


## Swivel Cross AVCS4D-4

PART NO.	CONNECTION SIZE
AVCS4D-4	1/4" Forged Female Flare Swivel With Depressor x 1/4" Access on all Flare Ends with One Core and Cap




## Female Connector AVUR3

PART NO.	CONNECTION SIZE
AVUR3-4	1/4" Female Flare with Copper Gasket




## 3 Way Solder Connector AVUS3

PART NO.	CONNECTION SIZE
AVUS3-40	For 3/16" O.D. Tube or 1/4" and 3/8" Solder Fitting/Swaged Tube



## 9 Way Solder Connector AVUS3

PART NO.	CONNECTION SIZE
AVUS3-49	For 3/16", 1/4", 5/16", 3/8" or 1/2" O.D. Tube. Also Fits 3/16", 1/4" and 5/16" Solder Fitting/Swaged Tube or 1/8" Hole May Be Punched in Larger Size Tube




## Straight Solder Connector AVUS

PART NO.	CONNECTION SIZE
AVUS-42	1/8" O.D. Tube or 1/4" Solder Fitting/Swaged Tube
AVUS-43	3/16" O.D. Tube or 1/4" Solder Fitting/Swaged Tube
AVUS-44	1/4" O.D. Tube or 3/8" Solder Fitting/Swaged Tube
AVUS-45	5/16" O.D. Tube or 1/2" Solder Fitting/Swaged Tube
AVUS-46	3/8" O.D. Tube or 1/2" Solder Fitting/Swaged Tube





## Swivel Connector AVUS4D

PART NO.	CONNECTION SIZE
AVUS4D-4	1/4" Forged Female Flare Swivel Nut with Depressor




## Forged Female Run Swivel Tee AVTS4

PART NO.	CONNECTION SIZE
AVTS4-4	1/4" Female Flare Swivel x 1/4" Access on Both Run and Branch
AVTS4D-4	1/4" Female Flare Swivel on Run with Depressor x 1/4" Access on Both Run and Branch




**Forged Female Branch Tee AVTS6**

PART NO.	CONNECTION SIZE
AVTS6-4	1/4" Female Flare Swivel x 1/4" Access on Both Ends
AVTS6D-4	1/4" Female Flare Swivel on Branch with Depressor x 1/4" Access on Both Ends




**Quick Seal Caps 640QSF**

PART NO.	CONNECTION SIZE
640QSF-4	1/4" SAE Seal Cap with Seal Gasket
640QSF-6	3/8" SAE Seal Cap with Seal Gasket




**Quick Seal Caps 640QSFC**

PART NO.	CONNECTION SIZE
640QSFC-4	1/4" SAE Seal Cap with Chain and Ring Assembly Seal Gasket




**Quick Seal Cap with Core Remover 640QSFCR**

PART NO.	CONNECTION SIZE
640QSFCR-4	1/4" SAE Seal Cap Core Remover with internal Seal Gasket




**Core Remover CR**

PART NO.	CONNECTION SIZE
CR-001	Standard Core Remover




**Valve Cores VC**

PART NO.	CONNECTION SIZE
VC-001	Replacement Valve Cores For all 1/4" Access Valves



**Forged Male Straight Thread O-Ring Port Male Branch Tee AVT1F1**

PART NO.	CONNECTION SIZE
AVTIFI-4	1/4" forged male straight thread o-ring port male branch tee




## Access Valves

---

### Forged Male Straight Thread O-Ring Port Male Run Tee AVT3F1

---

PART NO.	CONNECTION SIZE
AVT3FI-4	1/4" forged male straight thread o-ring port male run tee




---

### Refrigerant adapter 88AC

---

PART NO.	CONNECTION SIZE
88AC-8-2	1/8" male pipe to SAE J2197 Acme threaded male connector




---

### Refrigerant adapter 880AC

---

PART NO.	CONNECTION SIZE
880AC-8-4	1/4" female SAE flare to SAE J2197 Acme threaded male connector



---

### Refrigerant adapter 881AC

---

PART NO.	CONNECTION SIZE
881AC-8-4	1/4" SAE male flare to SAE J2197 Acme threaded female connector

