

GLOBAL

BATTERY & WELDING CABLE

BATTERY (STARTER) CABLE

- Full-gauge copper conductor
- Tough, high temperature PVC insulation – abrasion and chemical resistant
- Temperature rating of 105°C (221°F)
- Recommended for connecting battery to switch, starter, and ground
- For use at 50 volts or less
- Meets or exceeds SAE J1127 Specifications
- 25 ft length are coiled



PART #	DESCRIPTION	PACK
A15-275009	6AWG X 25' BATTERY CABLE BLACK	(B)
A15-275010	6AWG X 25' BATTERY CABLE RED	(B)
A15-275011	4AWG X 25' BATTERY CABLE BLACK	(B)
A15-275012	4AWG X 25' BATTERY CABLE RED	(B)
A15-275013	2AWG X 25' BATTERY CABLE BLACK	(B)
A15-275014	2AWG X 25' BATTERY CABLE RED	(B)
A15-275015	1AWG X 25' BATTERY CABLE BLACK	(B)
A15-275016	1AWG X 25' BATTERY CABLE RED	(B)
A15-275018	1/0AWGX25' BATTERY CABLE BLACK	(B)
A15-275019	1/0AWGX25' BATTERY CABLE RED	(B)
A15-275020	2/0AWGX25' BATTERY CABLE BLACK	(B)
A15-275021	2/0AWGX25' BATTERY CABLE RED	(B)
A15-275022	3/0AWGX25' BATTERY CABLE BLACK	(B)
A15-275024	4/0AWGX25' BATTERY CABLE BLACK	(B)

WELDING CABLE

- High stranding and neoprene jacket for greater conductivity & flexibility
- Synthetic rubber insulation stays flexible
- Excellent abrasion, salt and chemical resistant insulation
- Can be used as super flexible battery cable
- Rated to 600 volts



PART #	DESCRIPTION	PACK
A15-285200	2/0AWGX25' WELDING CABLE-BLK	(B)

