

GLOBAL BATTERY LUGS

ASSORTMENT

GLOBAL heat-shrink tubing should be used over all battery terminal connections.
(SEE PAGE O-081 in the “ELECTRICAL” SECTION)

Standard Battery Lug

Crimpable lug features unique flared barrel design to eliminate wire strand hang-ups. Unplated. Fully annealed electrolytic copper construction provides excellent conductivity. Wire gauge identification marked on lug barrel.



PART #	DESCRIPTION	PACK
A17-275030	6AWG X 5/16 STUD BATTERY LUG	(CF)
A17-275032	6AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275034	4AWG X 5/16 STUD BATTERY LUG	(CF)
A17-275036	4AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275037	2AWG X 5/16 STUD BATTERY LUG	(CF)
A17-275038	2AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275039	1AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275040	1/0AWG X 5/16 STUD BATTERY LUG	(CF)
A17-275042	1/0AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275044	1/0AWG X 1/2 STUD BATTERY LUG	(CF)
A17-275046	2/0AWG X 5/16 STUD BATTERY LUG	(CF)
A17-275048	2/0AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275050	2/0AWG X 1/2 STUD BATTERY LUG	(CF)
A17-275052	3/0AWG X 3/8 STUD BATTERY LUG	(CF)
A17-275054	3/0AWG X 1/2 STUD BATTERY LUG	(CF)
A17-275056	4/0AWG X 3/8 STUD BATTERY LUG	(BA)
A17-275060	4/0AWG X 1/2 STUD BATTERY LUG	(BA)
A17-275070	1AWG FLARED BUTT CONNECTOR	(BA)
A17-275072	1/0AWG FLARED BUTT CONNECTOR	(BA)
A17-275074	2/0AWG FLARED BUTT CONNECTOR	(BA)
A17-275076	3/0AWG FLARED BUTT CONNECTOR	(BA)
A17-275078	4/0AWG FLARED BUTT CONNECTOR	(BA)



Flared Butt Connector

Seamless construction. Tin-plated for corrosion resistance. Fully annealed electrolytic copper construction provides excellent conductivity. Wire gauge identification marked on lug barrel.



GLOBAL INDUSTRIAL PRODUCTS