## **ANCHORS**



# GLOBAL MACHINE SCREW ANCHORS



- CAN BE USED IN CONCRETE, BLOCK, BRICK OR STONE
- LEAD SLEEVE CONFORMS TO IRREGULARITIES OF HOLE
- CAN BE USED WITH MACHINE SCREWS OR BOLTS
- RUST-PROOF

## **APPLICATIONS:**

 IDEAL FOR SHALLOW HOLE ANCHORING OF LIGHT AND MEDIUM LOADS IN SOLID MASONRY AND CONCRETE



		<u>PULLOUT</u>			
M.S ANCHOR PART #	DESCRIPTION	<b>PACK</b>	<b>HOLE SIZE</b>	3500psi CONCRETE	SET TOOL PART #
L09-245010	10-24 MACHINE SCREW ANCHOR	(B)	3/8"	970	L09-142024
L09-245012	1/4-20 MACHINE SCREW ANCHOR	(B)	1/2"	2200	L09-142250
L09-245014	5/16-18 MACHINE SCREW ANCHOR	(FA)	5/8"	3100	L09-142350
L09-245016	3/8-16 MACHINE SCREW ANCHOR	(FA)	3/4"	5500	L09-142400
L09-245018	1/2-13 MACHINE SCREW ANCHOR	(FA)	7/8"	6310	L09-142500

### INSTALLATION



Drill hole in masonry. Insert Tampin conical end first.



Use setting tool to expand lead sleeve into masonry.



Install work by inserting and tightening a standard machine bolt or screw.



# GLOBAL INDUSTRIAL PRODUCTS