

GLOBAL



FUEL LINE HOSE

- SAE 30R7
- Hypalon cover and nitrile tube provide superior performance with leaded or unleaded fuels
- Can be used with diesel fuel
- Meets O.E.M. requirements
- Resists damage from high temperatures, oil, grease and ozone
- Temperature range of -29°F to 257°F
- 50 P.S.I. maximum working pressure

<u>PART #</u>	<u>DESCRIPTION</u>	<u>PACK</u>
A19-565030	1/4 X 25' FUEL LINE HOSE	(B)
A19-565032	5/16 X 25' FUEL LINE HOSE	(B)
A19-565034	3/8 X 25' FUEL LINE HOSE	(B)
A19-565036	7/16 X 25' FUEL LINE HOSE	(B)

VACUUM HOSE

- Flexible & noncollapsible
- Oil & heat resistant
- Compression proof
- Meets SAEJ1037
- Temperature rating: -40°F to 212°F

<u>PART #</u>	<u>DESCRIPTION</u>	<u>PACK</u>
A19-565040	1/8 X 50' VACUUM HOSE	(B)
A19-565042	3/16 X 50' VACUUM HOSE	(B)
A19-565044	1/4 X 50' VACCUM HOSE	(B)

HEATER HOSE

- Tough ozone and heat resistant EPDM cover and high-tensile reinforcement protects against kinking and surge pressure
- EPDM tube safely handles all coolant solutions and corrosive additives
- Temperature rating: -40°F to 212°F

<u>PART #</u>	<u>DESCRIPTION</u>	<u>PACK</u>
A19-566625	5/8 X 50' HEATER HOSE	(B)



GLOBAL INDUSTRIAL PRODUCTS