

GLOBAL

GENERAL SERVICE TYPE (GST) HOSE



- Economical and versatile general purpose hose.
- Excellent for air & water service as well as many agricultural chemicals including LASSO® herbicide. EPDM tube
- Cover resists heat, sunlight, ozone and weathering.
- Hose exceeds RMA class C medium oil resistance requirements.
- Suitable for applications such as oil mist lubricating air lines, but NOT suitable for the transfer of petroleum products.
- Closely plied reinforcement of high tensile textile cord provides excellent coupling retention and kink resistance
- 4:1 Safety factor

Tube: Black EPDM

Cover: EPDM - colors referenced above

Reinforcement: Multiple textile spirals

Temp. Range: -40°F to +212°F

PART #	DESCRIPTION (SIZE = ID)	OD	Min. Bend Radius	Max Rec. WP	PACK
I05-219225	1/4" GST HOSE	0.500	2.5	200 psi	(B)
I05-219231	5/16" GST HOSE	0.594	3.3	200 psi	(B)
I05-219238	3/8" GST HOSE	0.656	3.5	200 psi	(B)
I05-219250	1/2" GST HOSE	0.813	4.5	200 psi	(B)
I05-219263	5/8" GST HOSE	0.969	5.5	200 psi	(B)
I05-219275	3/4" GST HOSE	1.109	6.0	200 psi	(B)
I05-219277	1" GST HOSE	1.406	7.0	200 psi	(B)
I05-219279	1-1/4" GST HOSE	1.741	7.5	200 psi	(B)
I05-219281	1-1/2" GST HOSE	1.985	8.5	200 psi	(B)

