

## GLOBAL

### PUSH-ON AIR HOSE



- Oil resistant hose
- Excellent for use with air tools, to convey water, mild chemicals and various petroleum products.
- Light and flexible.
- Special braid angle for quick and secure push-on coupling retention.
- Available in various colors for color coding line.
- Flame resistant cover is branded with MSHA approval number.
- 4:1 Safety factor

**Tube:** Black Nitrile

**Cover:** Black, blue, or red Neoprene

**Reinforcement:** One textile braid

**Temp. Range:** -40° F to +212° F

<u>PART #</u>	<u>DESCRIPTION (SIZE = ID)</u>	<u>OD</u>	<u>Min. Bend Radius</u>	<u>Max Rec. WP</u>	<u>PACK</u>
I06-441250	1/4 BLACK PUSH-ON HOSE	0.500	3.0	300 psi	(B)
I06-441375	3/8 BLACK PUSH-ON HOSE	0.625	3.0	300 psi	(B)
I06-441500	1/2 BLACK PUSH-ON HOSE	0.750	5.0	300 psi	(B)
I06-441625	5/8 BLACK PUSH-ON HOSE	0.906	6.0	300 psi	(B)
I06-441750	3/4 BLACK PUSH-ON HOSE	1.031	7.0	300 psi	(B)
I06-443250	1/4 RED PUSH-ON HOSE	0.500	3.0	300 psi	(B)
I06-443375	3/8 RED PUSH-ON HOSE	0.625	3.0	300 psi	(B)
I06-443500	1/2 RED PUSH-ON HOSE	0.750	5.0	300 psi	(B)
I06-443625	5/8 RED PUSH-ON HOSE	0.906	6.0	300 psi	(B)
I06-443750	3/4 RED PUSH-ON HOSE	1.031	7.0	300 psi	(B)
I06-445250	1/4 BLUE PUSH-ON HOSE	0.500	3.0	300 psi	(B)
I06-445375	3/8 BLUE PUSH-ON HOSE	0.625	3.0	300 psi	(B)
I06-445500	1/2 BLUE PUSH-ON HOSE	0.750	5.0	300 psi	(B)
I06-445625	5/8 BLUE PUSH-ON HOSE	0.906	6.0	300 psi	(B)
I06-445750	3/4 BLUE PUSH-ON HOSE	1.031	7.0	300 psi	(B)



## GLOBAL INDUSTRIAL PRODUCTS