

ITW Permatex  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924 (ChemTel)  
 International Emergency: 00+ 1+ 813-248-0585

Global Part # A05-257100

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 21425 FAST CURE EPOXY PART 1  
**Item No:** 150345E  
**Product Type:** Epoxy resin

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Component   | Weight% | ACGIH; TLV-TWA                  | OSHA PEL             |
|---|---------|---------------------------------|----------------------|
| ALUMINUM HYDROXIDE<br>21645-51-2                              | 40-50   | 10 mg/m <sup>3</sup> TWA (dust) | Not listed           |
| EPOXY RESIN<br>(EPICHLOROHYDRIN, BISPENOL<br>A)<br>25085-99-8 | 30-50   | Not listed                      | Not listed           |
| TITANIUM DIOXIDE<br>13463-67-7                                | <10     | 10 mg/m <sup>3</sup>            | 15 mg/m <sup>3</sup> |
| BISPENOL A/EPICHLOROHYDRIN<br>BASED EPOXY RESIN<br>25068-38-6 | <5      | Not listed                      | Not listed           |
| EPOXY RESIN<br>28906-96-9                                     | <3      | Not listed                      | Not listed           |

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye, skin and respiratory irritation. May cause skin sensitization.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation  
**Signs and Symptoms of Exposure:** Eyes: Exposure to liquid or vapor causes mild eye irritation. Symptoms may include burning, tearing, redness, stinging, blurred vision and corneal injury. Repeated skin contact may cause allergic skin reactions. Ingestion may cause nausea and vomiting.

| Component   | Weight% | NTP   | ACGIH Carcinogens | IARC Carcinogen                              |
|---|---------|---|-------------------|--|
| ALUMINUM HYDROXIDE<br>21645-51-2                              | 40-50   | Not Listed  |                   |  |
| EPOXY RESIN (EPICHLOROHYDRIN, BISPENOL A)<br>25085-99-8       | 30-50   | Not Listed  |                   | Bisphenol A; Group 3, Vol. 71, pg 1285; 1999 |
| TITANIUM DIOXIDE<br>13463-67-7                                | <10     | male rat-negative,<br>female rat-negative,<br>male mice-negative,<br>female mice-negative | A4                | Group 2B; Vol 93,2006; Vol 47,1989           |
| BISPENOL A/EPICHLOROHYDRIN BASED EPOXY<br>RESIN<br>25068-38-6 | <5      | Not Listed  |                   |  |
| EPOXY RESIN<br>28906-96-9                                     | <3      | Not Listed  |                   |  |

**Aggravated Medical Condition:** Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. If not breathing, give artificial respiration. Obtain medical attention.  
**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before re-use.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**5. FIRE FIGHTING MEASURES**

|  |   |
|--|---|
| <b>Flash Point °F(C°):</b>               | >400°F (204.4°C) PMCC   |
| <b>Recommended Extinguishing Media:</b>  | Carbon Dioxide, Dry Chemicals, Foam.  |
| <b>Special Fire-Fighting Procedures:</b> | Material will not burn unless preheated. Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact. |
| <b>Hazardous Products of Combustion:</b> | When heated to decomposition it emits fumes of Cl-, carbon monoxide, other fumes and vapors varying in composition and toxicity                                   |
| <b>Unusual Fire/Explosion Hazards:</b>   | Heating above 149°C (300°F) in the presence of air may cause slow oxidation decomposition and above 260°C (500°F) may cause polymerization.                       |
| <b>Lower Explosive Limit:</b>            | n/d   |
| <b>Upper Explosive Limit:</b>            | n/d   |

**6. ACCIDENTAL RELEASE MEASURES**

|                          |  |
|--------------------------|--|
| <b>Spill Procedures:</b> | Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers. |
|--------------------------|--|

**7. HANDLING AND STORAGE**

|                  |   |
|------------------|---|
| <b>Storage:</b>  | Store away from heat.   |
| <b>Handling:</b> | Avoid contact with skin and eyes. Use in a well ventilated area. Avoid contact with vapors from heated material. Wash hands before eating and smoking. Discard contaminated leather gloves and shoes. |

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

|                                |  |
|--------------------------------|--|
| <b>Eyes:</b>                   | Safety glasses.  |
| <b>Skin:</b>                   | Neoprene or nitrile gloves recommended.  |
| <b>Ventilation:</b>            | General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. |
| <b>Respiratory Protection:</b> | An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.   |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                               |                        |
|-------------------------------|------------------------|
| <b>Appearance:</b>            | Black viscous liquid   |
| <b>Odor:</b>                  | Slight                 |
| <b>Boiling Point:</b>         | >500°F (260°C)         |
| <b>pH:</b>                    | Neutral                |
| <b>Solubility in Water:</b>   | Negligible             |
| <b>Specific Gravity:</b>      | 1.53                   |
| <b>VOC(Wt.%):</b>             | <1%                    |
| <b>Vapor Pressure:</b>        | 0.03 mm Hg @ 171°F     |
| <b>Vapor Density (Air=1):</b> | >1                     |
| <b>Evaporation Rate:</b>      | <1 (butyl acetate = 1) |

**10. STABILITY AND REACTIVITY**

|  |  |
|--|--|
| <b>Chemical Stability:</b>               | Stable at normal conditions  |
| <b>Hazardous Polymerization:</b>         | Will not occur   |
| <b>Incompatibilities:</b>                | Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines) |
| <b>Conditions to Avoid:</b>              | Heat.  |
| <b>Hazardous Products of Combustion:</b> | When heated to decomposition it emits fumes of Cl-, carbon monoxide, other fumes and vapors varying in composition and toxicity              |

**11. TOXICOLOGICAL INFORMATION**

See Section 3

**12. ECOLOGICAL INFORMATION**

No data available

**13. DISPOSAL CONSIDERATIONS**

|  |  |
|--|--|
| <b>Recommended Method of Disposal:</b> | Disposal should be made in accordance with federal, state and local regulations. |
| <b>US EPA Waste Number:</b>            | NH - Not a RCRA Hazardous Waste Material   |

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### U.S. Department of Transportation - DOT - 49 CFR (Ground)

**DOT Shipping Name:** Not regulated

**Hazard Class:** None

**UN/ID Number:** None

### IATA (Air)

**Proper Shipping Name:** Not regulated

**Class or Division:** None

**UN/ID Number:** None

### IMDG (Vessel)

**Proper Shipping Name:** Not regulated

**Hazard Class:** None

**UN Number:** None

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**California Proposition 65:** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 1, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILILTY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106  
**Telephone No.:** 1-87-Permatex (877) 376-2839

**Revision Date:** October 29, 2012

**Revision Number:** 6

ITW Permatex  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924 (ChemTel)  
 International Emergency: 00+ 1+ 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 21425 FAST CURE EPOXY PART 2  
**Item No:** 150445E  
**Product Type:** Epoxy hardener

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Component  | Weight% | ACGIH; TLV-TWA                  | OSHA PEL   |
|--|---------|---------------------------------|------------|
| ALUMINUM HYDROXIDE<br>21645-51-2                         | 40-50   | 10 mg/m <sup>3</sup> TWA (dust) | Not listed |
| POLYMERCAPTAN CURING<br>AGENT<br>Proprietary             | 20-40   | Not listed                      | Not listed |
| BENZYL ALCOHOL<br>100-51-6                               | <10     | Not listed                      | Not listed |
| 2,4,6-<br>TRIS(DIMETHYLAMINOMETHYL)PH<br>ENOL<br>90-72-2 | <10     | Not listed                      | Not listed |
| STYRENE<br>100-42-5                                      | <5      | 20 ppm                          | 100 ppm    |

### 3. HAZARDS IDENTIFICATION

**Toxicity:** Corrosive. Severe irritation or burns, necrosis, blistering and permanent injury. Product can be absorbed through the skin and may cause nausea, headache and general discomfort. May cause lacrimation, conjunctivitis, corneal damage and may cause permanent injury (i.e. blindness). If the hardener is poorly ventilated, strongly heated or atomized, the vapor or mist can cause severe irritation of the respiratory tract, damage contacted tissue and produce scarring. Coughing and chest pain may result, nausea and vomiting in severe cases. Causes severe damage to mucous membranes if swallowed. May cause malaise, headache, discomfort, bleeding and vomiting of blood.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Overexposure may cause eye and skin redness, difficulty breathing and vomiting. Contact with product at elevated temperatures can result in thermal burns.

| Component  | Weight% | NTP   | ACGIH Carcinogens                                 | IARC Carcinogen                                |
|--|---------|---|---|--|
| ALUMINUM HYDROXIDE<br>21645-51-2                 | 40-50   | Not Listed  |   |  |
| POLYMERCAPTAN CURING AGENT<br>Proprietary        | 20-40   | Not Listed  |   |  |
| BENZYL ALCOHOL<br>100-51-6                       | <10     | male rat-no evidence;<br>female rat-no<br>evidence; male mice-<br>no evidence; female<br>mice-no evidence |   |  |
| 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL<br>90-72-2 | <10     | Not Listed  |   |  |
| STYRENE<br>100-42-5                              | <5      | male rat-negative;<br>female rat-negative;<br>male mice-equivocal;<br>female mice-negative                | A4 - Not Classifiable<br>as a Human<br>Carcinogen | Group 2B; Vol. 60, 1994;<br>Monograph 82, 2002 |

**Aggravated Medical Condition:** Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

**4. FIRST AID MEASURES**

|                      |  |
|----------------------|--|
| <b>Ingestion:</b>    | Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person. |
| <b>Inhalation:</b>   | Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.                       |
| <b>Skin Contact:</b> | Rinse immediately with plenty of water for at least 15 minutes Wash off with soap and water If skin irritation persists, call a physician                  |
| <b>Eye Contact:</b>  | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.                  |

**5. FIRE FIGHTING MEASURES**

|  |  |
|--|--|
| <b>Flash Point °F(C°):</b>               | >200°F (93.3°C)  |
| <b>Recommended Extinguishing Media:</b>  | Carbon Dioxide, Dry Chemicals, Foam.   |
| <b>Special Fire-Fighting Procedures:</b> | Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact. Use water spray to cool exposed containers. |
| <b>Hazardous Products of Combustion:</b> | Acrid and toxic fumes with organic amines, ammonia, oxides of carbon and nitrogen  |
| <b>Unusual Fire/Explosion Hazards:</b>   | Sudden reaction and fire may result if product is mixed with an oxidizing agent.   |
| <b>Lower Explosive Limit:</b>            | n/d  |
| <b>Upper Explosive Limit:</b>            | n/d  |

**6. ACCIDENTAL RELEASE MEASURES**

|                          |   |
|--------------------------|---|
| <b>Spill Procedures:</b> | Wear appropriate protective and respiratory equipment. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers. |
|--------------------------|---|

**7. HANDLING AND STORAGE**

|                  |  |
|------------------|--|
| <b>Storage:</b>  | Store away from heat. Do not store in reactive metal containers. Keep away from acids and oxidizers.   |
| <b>Handling:</b> | Avoid prolonged skin contact. Keep away from eyes. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Wash hands and face after handling this compound. Discard contaminated leather gloves and shoes. Do not mix with sodium nitrite or other nitrosating agents as cancer-causing nitrosamines could be formed. |

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

|                                |  |
|--------------------------------|--|
| <b>Eyes:</b>                   | Safety glasses with side shields or chemical goggles.  |
| <b>Skin:</b>                   | Neoprene or nitrile gloves recommended.  |
| <b>Ventilation:</b>            | General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. |
| <b>Respiratory Protection:</b> | An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.   |

**9. PHYSICAL AND CHEMICAL PROPERTIES**

|                               |                        |
|-------------------------------|------------------------|
| <b>Appearance:</b>            | Black paste            |
| <b>Odor:</b>                  | Mercaptan              |
| <b>Boiling Point:</b>         | >300°F (148.8°C)       |
| <b>pH:</b>                    | Does not apply         |
| <b>Solubility in Water:</b>   | Slight                 |
| <b>Specific Gravity:</b>      | 1.4                    |
| <b>VOC(Wt.%):</b>             | 10.8%                  |
| <b>Vapor Pressure:</b>        | <5 mm Hg @ 77°F        |
| <b>Vapor Density (Air=1):</b> | >1                     |
| <b>Evaporation Rate:</b>      | <1 (butyl acetate = 1) |

**10. STABILITY AND REACTIVITY**

|  |  |
|--|--|
| <b>Chemical Stability:</b>               | Stable at normal conditions  |
| <b>Hazardous Polymerization:</b>         | Will not occur   |
| <b>Incompatibilities:</b>                | Strong oxidizers, Sodium/calcium hypochlorite, Peroxides, Reactive metals (e.g. Na, Ca, zinc), Acids |
| <b>Conditions to Avoid:</b>              | Heat. Corrodes base metals.  |
| <b>Hazardous Products of Combustion:</b> | Acrid and toxic fumes with organic amines, ammonia, oxides of carbon and nitrogen                    |

**11. TOXICOLOGICAL INFORMATION**

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### U.S. Department of Transportation - DOT - 49 CFR (Ground)

**DOT Shipping Name:** Amines, liquid, corrosive, n.o.s., (Tris-2,4,6-(Dimethylaminomethyl) Phenol), Limited Quantity  
**Hazard Class:** Class 8 PGIII  
**UN/ID Number:** UN 2735

### IATA (Air)

**Proper Shipping Name:** Consumer Commodity  
**Class or Division:** Class 9  
**UN/ID Number:** ID 8000

### IMDG (Vessel)

**Proper Shipping Name:** Amines, liquid, corrosive, n.o.s., (Tris-2,4,6-(Dimethylaminomethyl) Phenol), Limited Quantity  
**Hazard Class:** Class 8 PGIII  
**UN Number:** UN 2735

**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

STYRENE

**California Proposition 65:** WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 3, FLAMMABILITY 1, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 3, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106  
**Telephone No.:** 1-87-Permatex (877) 376-2839

**Revision Date:** October 29, 2012

**Revision Number:** 6