


SOCKET PRODUCTS

GLOBALLOY BUTTON HEAD SOCKET CAP SCREWS

- For Greater Strength and Holding Power
- Resist Loosening Under Stress and Vibration
- Over 180,000 P.S.I. - Without Brittleness

- Deep, clean sockets provide maximum key engagement
- Fully roll-formed threads provide maximum strength and precision fit in tapped holes
- IMPREGNO-PLATED for maximum protection against rust and corrosion
- Machine pointed for easy assembly

LOW HEAD HEIGHT



GLOBALLOY BUTTON HEAD SOCKET CAP SCREWS are used in fastening applications where the metal is too thin to countersink or counterbore. Also used for attaching die guides and inserts to insert turning tools.

Low head height prevents snagging or catching of clothing on equipment or injury to mechanic's hands. Ideal for attaching guards, hinges and cover plates to machine tools and production equipment.

CLASS C15 - COARSE THREAD

SIZE	4-40	6-32	8-32	10-24	1/4-20	5/16-18	3/8-16	1/2-13	5/8-11
1/4	331200 (BAA)	331206 (BAA)	331214 (BAA)						
3/8	331202 (BAA)	331208 (BAA)	331216 (BAA)	331224 (BAA)	331240 (BAA)	331256 (BAA)			
1/2	331204 (BAA)	331210 (BAA)	331218 (BAA)	331226 (BAA)	331242 (BAA)	331258 (BAA)	331274 (FA)		
5/8		331212 (BAA)	331220 (BAA)				331276 (FA)		
3/4			331222 (BAA)	331228 (BAA)	331244 (BAA)	331260 (BAA)	331278 (FA)		
7/8							331280 (FA)		
1				331230 (BAA)	331246 (BAA)	331262 (BAA)	331282 (FA)	331295 (CF)	331302 (CF)
1 1/4							331284 (FA)	331296 (CF)	331304 (CF)
1 1/2								331298 (CF)	331306 (CF)
2								331300 (CF)	331308 (CF)

CLASS C15 - FINE THREAD

SIZE	10-32	1/4-28	5/16-24	3/8-24					
3/8	331232 (BAA)	331248 (BAA)	331264 (BAA)						
1/2	331234 (BAA)	331250 (BAA)	331266 (BAA)	331286 (FA)					
5/8	331235 (BAA)		331268 (BAA)	331288 (FA)					
3/4	331236 (BAA)	331252 (BAA)	331270 (BAA)	331290 (FA)					
7/8				331292 (FA)					
1	331238 (BAA)	331254 (BAA)	331272 (BAA)	331294 (FA)					



GLOBAL INDUSTRIAL PRODUCTS